

# DP4N-MLXX

DIN Rail Terminal Blocks > Push-in Design

Date:2024-12-06



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.  
The final product is made according to engineering drawing.

## Product Description

300V, 10A, Beige (default)

## General information

|                   |                                     |
|-------------------|-------------------------------------|
| Short description | Fuse Terminal Block, Push-in Design |
| Category          | Fuse Terminal Block                 |
| Color             | Beige (default)                     |
| Connection method | Push-in Design                      |
| Type of locking   | Rail Mounting                       |
| Length (mm)       | 57                                  |
| Width (mm)        | 6.7                                 |
| Height (mm)       | 83.2/ 84.7(TS-35N)/92.2(TS-35/15N)  |
| Level             | Single level                        |
| Connection points | 2                                   |

## Material information

|                                              |                   |
|----------------------------------------------|-------------------|
| Insulation material                          | PA                |
| Insulation material group                    | I                 |
| Flame retardant rating , compliant with UL94 | V0                |
| Insulation resistance                        | ≥500MΩ at DC 500V |

## Connection data-IEC

|                                                                                                         |                                                  |
|---------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| Rated voltage (V)                                                                                       | 300                                              |
| Rated current (A)                                                                                       | 6.3 (the Current is determined by the fuse used) |
| Rated voltage (III/3)(V)                                                                                | 300                                              |
| Rated impulse voltage (III/3)(KV)                                                                       | 4                                                |
| Conductor cross section solid. min (mm <sup>2</sup> )                                                   | 0.2                                              |
| Conductor cross section solid.max (mm <sup>2</sup> )                                                    | 6                                                |
| Conductor cross section stranded. min (mm <sup>2</sup> )                                                | 0.2                                              |
| Conductor cross section stranded. max (mm <sup>2</sup> )                                                | 4                                                |
| Conductor cross section flexible, with min ferrule without plastic sleeve (mm <sup>2</sup> )            | 0.25                                             |
| Conductor cross section flexible, with max ferrule without plastic sleeve (mm <sup>2</sup> )            | 4                                                |
| Conductor cross section flexible, with min ferrule with plastic sleeve (mm <sup>2</sup> )               | 0.25                                             |
| Conductor cross section flexible, with max ferrule with plastic sleeve (mm <sup>2</sup> )               | 4                                                |
| 2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm <sup>2</sup> ) | 0.5                                              |
| 2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm <sup>2</sup> ) | 1                                                |
| Slotted screwdriver size (Blade thickness x Width)(mm)                                                  | 0.8X4                                            |
| Stripping Length (mm)                                                                                   | 12                                               |
| Mounting rail                                                                                           | TS-35N 、TS-35/15N                                |
| End cover plate required                                                                                | YES                                              |
| Grounding connections                                                                                   | NO                                               |

## Connection data-UL



|                                                  |     |
|--------------------------------------------------|-----|
| Rated voltage (UL/CUL Group B)(V)                | 300 |
| Rated current (UL/CUL Group B)(A)                | 10  |
| Min. solid wire connection (AWG) acc. to UL/CUL  | 24  |
| Max. solid wire connection AWG acc. to UL/CUL    | 10  |
| Min. stranded wire connection AWG acc. to UL/CUL | 24  |
| Max. stranded wire connection AWG acc. to UL/CUL | 10  |

## Environment & Safety

|                                         |     |
|-----------------------------------------|-----|
| Back of the hand protection (YES or NO) | YES |
|-----------------------------------------|-----|

|                                 |     |
|---------------------------------|-----|
| Finger protection (YES or NO)   | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

## Drawings



## Approvals

